

BALLISTIC SPECTACLES

bolle
TACTICAL

www.bolle-tactical.com

SWAT

Certified to STANAG 2920 and EN 172, these ballistic protection sunglasses ensure maximum protection against any event. Thanks to its non-slip bridge, flexible temples and its ultra enveloping design SWAT will provide you comfort and protection. SWAT is available in smoke, polarized and silver flash.

ULTRA FLEXIBLE AND COMFORTABLE NYLON FRAME

ANTI-SCRATCH, ANTI-FOG COATINGS

BALLISTIC POLYCARBONATE LENS

NON-SLIP BRIDGE



NON-SLIP TEMPLES



NON SLIP BRIDGE

INTEGRATED LATERAL PROTECTION

COMFORTABLE AND NON SLIP TEMPLES

HIGH RESISTANCE

28 G

Europe Bollé Safety
95 Rue Louis Guérin
69100 Villeurbanne - France
tel: 00 33 (0) 4 78 85 23 64
fax: 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT9 2NY
tel. 00 44 (0)208 391 4700
fax 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

Ballistic Resistance STANAG 2920

Smoke lens: v50 196 m/s (705 km/h)
Polarized lens: v50 183 m/s (659 km/h)
Silver flash lens: v50 182 m/s (655 km/h)



Options

SUPPLY WITH: MICROFIBER POUCH /
INDIVIDUAL RIGID CARRY CASE / INDIVIDUAL
CARTON BOX



SWAT

Safety spectacles

STANDARD MARKINGS :

Products Ref.	LENSES													FRAMES												
	Risks relating to radiations		Bollé Protection Logo	Optical Quality			Mechanical Risks				Electrical Risks	Thermal Risks	Coatings (Optional marking K: anti-scratch N: anti-fog)		CE logo	Bollé Protection logo	Standards	Chemical Risks			Electrical Risks	Mechanical Risks			Thermal Risks	CE logo
	EN 170 - UV	EN 172 - Solaires (100% UV)		Permanent Wear	Intermittent Wear	Short Period	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact	Electric arc short circuiting	Molten metals and hot solids	anti-scratch	anti-fog				Liquid drops	Large dust particles > 5 microns	Gas and fine dust particles < 5 microns	Electric arc short circuiting	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact	
SWATPSF		5-3.1		1		F	N/A	N/A	T	N/A				CE		EN 166	N/A	N/A	N/A	N/A	F	N/A	N/A	T	N/A	CE
SWATFLASH		5-3.1		1		F	N/A	N/A	T	N/A				CE		EN 166	N/A	N/A	N/A	N/A	F	N/A	N/A	T	N/A	CE
SWATPOL		5-3.1		1		F	N/A	N/A	T	N/A				CE		EN 166	N/A	N/A	N/A	N/A	F	N/A	N/A	T	N/A	CE

N/A: Non applicable

TACTICAL

Ballistic Resistance

STANAG 2920



Silver Flash

V50: 655 km/h (182m/s)



Polarized

V50: 659 km/h (183 m/s)



Smoke

V50: 705 km/h (196m/s)

CHARACTERISTICS :

Lenses	PC - 2,2 mm - Curve 8
Frame	Nylon
Temples	Nylon
Spare Lenses	No

PACKAGING AND EAN13 CODE :

	SWATPSF	SWATFLASH	SWATPOL
individual carry case	3660740000677	3660740000684	36607400003691
N/A	N/A	N/A	N/A
95 safety spectacles per outer pack	3660740200671	3660740200688	3660740200695

Notified laboratories for certification :

